

ELECTRICAL (ALARM) CONTACTS

- Two easily adjustable setpoints
- Can be used to open or close on rise
- 0.7A max current (higher loads can be run through relay)
- Available on 4" dial (P/N **PXEM21-40**) or 4 1/2" dial (P/N **PXEM21-45**)



MAX POINTER INDICATORS

- Indicates max pressure reached
- Easily reset
- Liquid fillable (Works best dry, though)
- Available for:
 - 2 1/2" dial (**MP-PR25**)
 - 4" dial (**MP-PR40**)
 - 4 1/2" dial (**MP-PT45**)



CUSTOM DIALS

- REOTEMP** can provide custom dials with:
- **Special Ranges or designs**
 - **Custom logos**
 - **Colored zones**
- Consult factory for assistance with dial designs



OPTIONAL WINDOWS

- **Polycarbonate**
- **Laminated Safety Glass**
- **Polysulfone (for autoclaving)**

PRESSURE SERVICES

Pressure Instrument Repair Services– Reotemp will be glad to quote on your repair and servicing needs for pressure gauges, transmitters, switches, and diaphragm seal systems.

Calibration and Certification – Services include testing, calibration, and certification of pressure gauges, transmitters, switches, and diaphragm seal systems. All certification is NIST traceable.

Certificate Description	Part#
Conformance/ calibration to NIST	CNISTPG
General calibration sticker	CALSTKPG
3 Logged Points - sticker & Cert.	CCALPG-3
5 Logged Points - sticker & Cert.	CCALPG-5
Switch setpoint cert	CCALSW

Oxygen Cleaning - removes oil from gauge intended for oxygen service.

Diaphragm Seal Application Assistance - REOTEMP will assist you in designing and specifying the most effective diaphragm seal system for your pressure or vacuum application. Contact factory for details.